



WHITE | TOUCH

USER INFORMATION -

Available sizes according EN420:2003+A1:2009: 7/S, 8/M, 9/L, 10/XL, 11/XXL

Features: gloves, 13G nylon liner with PU palm coating. Dexterity level 5.

Note: do not use these gloves near moving machinery and/or machine parts (if there is a risk of entanglement). These gloves must not come into contact with fire. Gloves meeting the requirement for resistance to puncture are not suitable for protection against sharp pointed objects such as injection needles. Gloves may contain latex. Latex may cause allergic reactions. In case of hypersensitivity, consult a doctor.

Cleaning, maintenance and storage: both new and used gloves must be thoroughly inspected before being worn, to ensure no damage is present. Do not use damaged gloves. Gloves should not be left in contaminated condition. Cleaning and disinfection is not intended for these gloves. The performance levels of worn and/or washed gloves may differ from the results shown below. Gloves should ideally be stored at 5 – 25 °C in a dry and well-ventilated area in original packaging. Avoid direct contact with sunlight.

Risk: gloves are intended to protect hands in working environments in accordance with EN388:2016 and EN420:2003+A1:2009. The user shall evaluate and determine the risks based on the intended application. The user shall use the glove only in intended application. The risk should be evaluated keeping in mind the protection levels and the harmonized standards on which gloves are tested. The gloves have been evaluated and tested to EN388:2016, EN420:2003+A1:2009 and Regulation EU 2016/425. The tests and Regulation relate to the risk that can be reasonable expected.

Obsolescence and disposal: the shelf life of the glove is 5 years if stored under the correct conditions. The exact service life of the glove cannot be specified and depends on the application and responsibility of the user to determine the suitability of the glove for its intended use.

General: this model does not contain any substances at levels that are known to, or suspected to, adversely effect user hygiene or health. Some gloves may contain latex, which can cause allergic reactions.

Please note: the results of the physical tests can help in glove selection, however actual conditions of use cannot be simulated. It is the responsibility of the (end)user and not the manufacturer to determine glove suitability for the intended use. Protection against risks or hazards not mentioned in this document is not guaranteed.

PPE Category II

EN388:2016



3131X

- ABRASION RESISTANCE
- CUT RESISTANCE COUP
- TEAR RESISTANCE
- PUNCTURE RESISTANCE
- CUT RESISTANCE TDM
- IMPACT

0	1	2	3	4	
0	1	2	3	4	5
0	1	2	3	4	
0	1	2	3	4	
A	B	C	D	E	F
P					

Pictogram EN388:2016 indicates that the product protects against mechanical risks. The figures indicate the performance levels tested in the palm area of the gloves. The protective gloves meet the applicable requirement of EN420:2003+A1:2009.

“X” indicates that the glove has not been subjected to the test, or the test method does not appear to be suitable for the design or material of the glove.

The EU type examination is carried out by CTC, Parc Sc. T. Garn. - 4, rue Herm. Frenkel, 69367 Lyon Cedex 07, France (Notified Body 0075) in accordance with Regulation 2016/425.

The Declaration of Conformity is available on www.hawedo.com

Hawedo B.V., Pr. Margrietstraat 36, 5104 AE Dongen, the Netherlands.

01.07.2019