

Protect PWH-3703F

Description

The Proway PWH-3703F is a work glove from the Protect Series. The Protect Series offers cut resistance to the latest standards without compromising on comfort. The PWH-3703F has an 18G liner made of UHMWPE/Recycled polyester/Pro-Cut yarn. With a recycled polyester liner, less new material is used which reduces waste. Nevertheless, it retains all the properties of new polyester, so the glove remains elastic, strong and resistant to abrasion. Pro-Cut adds cut resistance. The PWH-3703F features a nitrile coating, extra reinforcement between the thumb and is touchscreen compatible. Nitrile coating is flexible and offers good protection against abrasion. The coating contains no latex which reduces the risk of allergic reactions and protects to some extent against acids and oil. Reinforcement between thumb and index finger makes the glove less prone to abrasion and provides extra safety. Touchscreen functionality makes this glove suitable for working with smartphones, scanners and other touchscreen devices. Choose the Proway PWH-3703F and experience the ultimate combination of cut protection and comfort.



Applications

- Aviation industry
- Building and construction
- Fitting and maintenance
- General activities
- Glass industry
- Metal industry
- Metalworking and sheet metal work
- Operating touchscreen devices



Download the user instructions here

Features

Liner:	UHMWPE/Pro-Cut yarn/Recycled Polyester
Liner colour:	Blue / White
Gauge:	18G
Coating:	Foam nitrile palm coating with thumb reinforcement
Coating colour:	Black
Cuff:	Elastic

Product information

Article name	Size	Overlock colour	Packing	Header card
Protect PWH-3703F-07	7/S	Red	6 x 12 x 1 (72 pair)	1 pair
Protect PWH-3703F-08	8/M	Yellow	6 x 12 x 1 (72 pair)	1 pair
Protect PWH-3703F-09	9/L	Brown	6 x 12 x 1 (72 pair)	1 pair
Protect PWH-3703F-10	10/XL	Black	6 x 12 x 1 (72 pair)	1 pair
Protect PWH-3703F-11	11/XXL	Light Blue	6 x 12 x 1 (72 pair)	1 pair

Certification

Abrasion resistance: 4	EN 388:2016 + A1:2018	2016/425	EN ISO 21420:2020
Blade cut resistance: X			
Tear resistance: 4			
Puncture resistance: 2			
Cut resistance (ISO 13997): F	4X42F	CAT II	

Performance is measured on the palm of the glove. 'X' indicates that the glove has not been submitted to the test or the test method does not appear to be suitable for the glove design or material.

More information:

: +31(0)162312387
 : sales@hawedo.com
www.prowayprotection.com