

Description: Chlorinated heavy weight flock lined neoprene/natural rubber blended gloves

- Features & Benefits:
- \* A blend of natural rubber and neoprene
  - \* Anatomically shaped for comfort
  - \* Anti-slip pattern for good grip in wet and dry conditions
  - \* Bacteriostatic and fungistatic additives
  - \* Chlorinated for improved chemical resistance
  - \* Compliant with (EC) No. 1935/2004 & EU 10/2011 (Blue)
  - \* Ingredients comply with FDA regulations for food contact (Blue only)
  - \* Low in soluble proteins
  - \* Pure cotton lining to absorb perspiration
  - \* Straight cuff

Applications: Agriculture, Chemical Industry, Facility maintenance

Elastomer: Natural/Polychloroprene blended rubber

Thickness: 0.70 +/- 0.07 mm

Lining: Flocklined

Former: Honeycomb CIH

Exterior: Chlorinated

Cuff Types: Straight

Treatments: Chlorinated

Colours: Blue B3

AQL: 1.00

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016,EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	198	183	248	320
	7-7.5	208	190	251	320
	8-8.5	215	202	268	320
	9-9.5	235	226	280	320
	XL	250	237	293	330

Circumference in mm, +/- 5 mm      Tol. +/- 10 mm

Shelf Life 1 Years

EN 374-4

### Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



* Methanol (A)	Level 2	15.5
* Sodium hydroxide 40% (K)	Level 6	-6.8
* Sulphuric acid 96% (L)	Level 4	21
* Nitric acid 65% (M)	Level 6	18.4
* Acetic acid 99% (N)	Level 3	23.4
* Hydrogen peroxide 30% (P)	Level 6	3.4
* Formaldehyde 37% (T)	Level 6	8.1
* Hydrofluoric acid 40% (S)	Level 6	X

Note: Printed copies are valid only on the date printed

Printed Date: 05-Jan-2022

Revision:2

Published Date: 24-Jul-2020

**DPL**  
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards		Performance
---------------------------------------	--	-------------

EN 388



- \* Abrasion resistance
- \* Blade cut resistance
- \* Tear resistance
- \* Puncture resistance
- \* TDM cut resistance

Level 3  
Level 1  
Level 1  
Level 0  
X

Protection against Micro-organisms risk		Performance
---	--	-------------

EN ISO 374-1



- \* Protection against bacteria and fungi
- \* Protection against viruses

Pass  
n/a